

CLAIMS

1. A heat control system comprising
a heat generator which heat is generated
during the operation and temperature is necessarily
5 maintained in a predetermined range,
a vapor compression type refrigerator
having a compressor, a radiator, an evaporator and a
pressure reducing means to transfer heat from the lower
temperature side to the higher temperature side,
10 a heat exchanger for exchanging heat
between refrigerant discharged from the compressor and
prior to being fed into the radiator and medium for
exchanging heat from the heat generator, and
a bypass for guiding the refrigerant prior
15 to being fed into the evaporator to the heat exchanger
while detouring the evaporator and the compressor,
wherein
the system operates in a heating mode for
heating the medium with the high-temperature refrigerant
20 discharged from the compressor, and a heat dissipation
mode for cooling the medium with the refrigerant and
dissipating heat absorbed from the medium via the
radiator, and
during the heat dissipation mode, at least
25 part of the refrigerant flowing out from the radiator is
made to pass through the bypass.
2. A heat control system as defined by claim 1,
wherein the bypass mainly guides a liquid-phase component
of the refrigerant prior to being fed into the evaporator
30 to the heat exchanger.
3. A heat control system as defined by claim 1,
wherein the bypass guides the refrigerant discharged from
the radiator to the heat exchanger prior to being
decompressed by the pressure reducing means.
- 35 4. A heat control system as defined by claim 1,
wherein the system further comprises means for
controlling the heat exchange between the medium and the

refrigerant in the heat exchanger.

5 5. A heat control system as defined by claim 4,
 wherein the means for controlling the heat exchange
 operates in the heating mode when the temperature of the
10 heat generator is lower than a first predetermined
 temperature, operates in the heat dissipation mode when
 the temperature of the heat generator is a second
 predetermined temperature above the first predetermined
 temperature or higher, and operates in a normal mode when
15 the temperature of the heat generator is within a range
 from the first predetermined temperature to the second
 predetermined temperature, in which the heat exchange
 between the medium and the refrigerant is made to stop.

15 6. A heat control system as defined by claim 1,
 wherein the heat generator is a heat engine.

 7. A heat control system comprising
 a heat generator which heat is generated
 during the operation and temperature is necessarily
 maintained in a predetermined range,
20 a vapor compression type refrigerator
 having a compressor, a radiator, an evaporator and a
 pressure reducing means to transfer heat from the lower
 temperature side to the higher temperature side,
 a heat exchanger for exchanging heat
25 between refrigerant discharged from the compressor and
 prior to being fed into the radiator and medium for
 exchanging heat from the heat generator, and
 a cooler for cooling the refrigerant fed
 into the heat exchanger, wherein
30 the system operates in a heating mode for
 heating the medium with the high-temperature refrigerant
 discharged from the compressor, and a heat dissipation
 mode for cooling the medium with the refrigerant and
 dissipating heat absorbed from the medium via the
35 radiator.

 8. A heat control system as defined by claim 7,
 wherein the system further comprises means for

controlling the heat exchange between the medium and the refrigerant in the heat exchanger.

5 9. A heat control system as defined by claim 8,
wherein the means for controlling the heat exchange
operates in the heating mode when the temperature of the
heat generator is lower than a first predetermined
temperature, operates in the heat dissipation mode when
the temperature of the heat generator is a second
predetermined temperature above the first predetermined
10 temperature or higher, and operates in a normal mode when
the temperature of the heat generator is within a range
from the first predetermined temperature to the second
predetermined temperature, in which the heat exchange
between the medium and the refrigerant is made to stop.

15 10. A heat control system as defined by claim 7,
wherein the heat generator is a heat engine.